

GYRO CEILING FAN SPECIFICATIONS:

- 42" total maximum sweep
- 1000-1500 rpm side fan speeds
- Side fan heads independently adjustable
- Fan assembly rotates at 3 rpm, rotation can be stopped
- Integrated 100 watt halogen bulb, bulb included
- Cap for non-light use included
- Lifetime warranty on motor, 1 year on rest of fan
- Sloped ceilings OK up to 29 degrees without adapter
- Sloped ceilings up to 45 degrees OK with accessory adapter available at additional cost
- UL listed for indoor use, separate model F402 is indoor/outdoor Gyro which is UL listed for wet location use



MODELS AVAILABLE:

- F602-BN/CH brushed nickel with chrome accents and cages
- F602-RRB restoration bronze with schoolhouse globe light

DOWNRODS:

- Fan comes standard with 3 1/2" and 6" downrods—length to bottom of fan is 15 5/8" with 3 1/2" downrod and 18 1/8" with 6" downrod.
- Accessory downrods are available at additional cost in 12", 18", 24", 36", 48", 60", and 72" lengths.

WHAT'S IN THE BOX?

- Fan with blades as shown in picture
- 3 1/2" and 6" downrods
- Touch control wall switch for on/off, 3 fan speeds plus reverse, fan mounting rotation control, and dimmer for light
- Removable light kit as shown with bulb, 100 Watt halogen
- Matching cap for non-light use